

IN THE CLAIMS

1 1. (currently amended) A wireless mobile communications network including a
2 base station and a plurality of mobile nodes, comprising:

3 a first mobile node configured as a major node to communicate information
4 directly with the base station via a network link; and

5 a second mobile node configured as a minor node to communicate the
6 information indirectly with the base station via a local link with the major node and
7 the network link from the major node to the base station to form a locally linked
8 mobile network within the wireless mobile communications network, wherein the
9 communicating of the information is dynamically routed to optimize a quality of
10 service of the wireless mobile communications network and the locally linked
11 network; and

12 wherein the base station includes a memory to store a configuration list to
13 associate the major node with the minor node.

1 2. (original) The wireless mobile communications network of claim 1 wherein each
2 mobile node further comprises:

3 a header detector, coupled to a receiver and a decoder, configured to detect a
4 header in a frame used to communicate the information;

5 a message processor, coupled to the header detector and a transmitter,
6 configured to route the frame over the network link and the local link.

1 3. (original) The wireless mobile communication network of claim 2 wherein the
2 header detector is connected to an output of the decoder and the locally linked
3 mobile network operates asynchronously.

1 4. (original) The wireless mobile communication network of claim 2 wherein each
2 mobile node further comprises a GPS receiver and the locally linked mobile
3 network operates synchronously.

1 5. (original) The wireless mobile communication network of claim 2 wherein the
2 major node communicates the frame while in standby mode, and the minor node
3 receives the frame in active mode.

1 6. (original) The wireless mobile communications network of claim 2 wherein the
2 mobile nodes are cellular telephones.

1 7. (canceled)

1 8. (previously presented) The wireless mobile communications network of claim 2
2 wherein each frame includes a header.

1 9. (original) The wireless mobile communications network of claim 8 wherein the
2 header includes a code word, and control information.

1 10. (original) The wireless mobile communications network of claim 9 wherein the
2 code word is a Walsh code word.

1 11. (original) The wireless mobile communications network of claim 9 wherein the
2 code word is a forward code word and the control information includes a list of a
3 plurality of major nodes and a list of a plurality of minor nodes.

1 12. (original) The wireless mobile communications network of claim 9 wherein the
2 code word is a destination code word and the control information identifies the
3 minor node and the major node.

1 13. (original) The wireless mobile communications network of claim 9 wherein the
2 code word is a routing code word and the control information identifies the major
3 node and the control information indicates an amount of available bandwidth.

1 14. (original) The wireless mobile communications network of claim 9 wherein the
2 code word is a receive code word.

1 15. (original) The wireless mobile communications network of claim 2 wherein the
2 message processor of the major node replaces a forward code word in a header of
3 the frame with a receive code word, the forward code word identifying the major
4 node and the receive code word identifying the minor node.

1 16. (original) The wireless mobile communications network of claim 1 wherein the
2 base station monitors bandwidth of the locally linked mobile network.

1 17. (previously presented) The wireless mobile communications network of claim
2 1 wherein a configuration list of the nodes of the locally linked mobile network is
3 adaptively adjusted by the base station depending on need, traffic type, link
4 quality, coverage, utilized bandwidth, and mobility.

1 18. (original) The wireless mobile communications network of claim 1 wherein
2 each mobile node monitors a quality of the network link with the base station.

1 19. (original) The wireless mobile communication network of claim 4 wherein the
2 GPS receiver estimates position, speed, and bearing of the mobile node.

1 20. (original) The wireless mobile communication network of claim 4 wherein
2 each mobile node uses channel quality and mobility characteristics to determine
3 suitability for operating as the major node.

1 21. (original) The wireless mobile communication network of claim 1 wherein the
2 locally linked mobile network includes a plurality of major nodes configured to
3 communicate information with each other and the minor node.

1 22. (canceled)

1 23. (currently amended) The wireless mobile communication network of ~~claim 22~~
2 claim 1, wherein the minor node is associated with a plurality of major nodes.

1 24. (canceled)

1 25. (original) The wireless mobile communications network of claim 1 wherein the
2 locally linked mobile network operates in multicast mode.

3
4 26. (original) The wireless mobile communications network of claim 2 wherein
5 each frame is encrypted using a pseudo random number sequence.

1 27. (original) The wireless mobile communication network of claim 1 wherein the
2 major node operates in active mode while receiving low bandwidth frames
3 intended for the major node, and high bandwidth frames intended for the minor
4 node.

1 28. (original) The wireless mobile communications network of claim 1 including a
2 plurality of major nodes and the base station selects a particular one of the plurality
3 of major nodes to communicate with the minor node based on available bandwidth
4 between the major node and the base station.

1 29. (previously presented) The wireless mobile communications network of claim
2 1 including a plurality of base stations and a plurality of major nodes and minor
3 nodes communicating with each other via network links and local links.

1 30. (original) The wireless mobile communications network of claim 29 wherein a
2 first major node communicates with a first base station and a first minor node, and
3 a second major node communicates with a second base station and a second minor
4 node to enable the first and second minor nodes to communicate indirectly with
5 each other via the first and second major nodes and the first and second base
6 stations.

1 31. (original) The wireless mobile communications network of claim 29 wherein
2 minor nodes are dynamically assigned to different major nodes depending on a
3 quality of service of the network link and the local link.

1 32. (original) The wireless mobile communications network of claim 1 further
2 including an end of transmission signal to indicate an end of communicating the
3 information.

1 33. (currently amended) A method for communicating information in a wireless
2 mobile communications network including a base station and a plurality of mobile
3 nodes, comprising:

4 communicating information directly between a first mobile node
5 configured as a major node and the base station via a network link; and

6 communicating the information indirectly between the base station and a
7 second mobile node configured as a minor node via the network link between the
8 base station and the major node and a local link between the major node and the

9 minor node, wherein the communicating of the information is dynamically routed
10 to optimize a quality of service of the wireless mobile communications network
11 and the locally linked network; and
12 wherein the base station includes a memory to store a configuration list to
13 associate the major node with the minor node.

1 34. (original) The method of claim 33 further comprising:
2 detecting a header of a frame received in the major node; and
3 routing the frame to the minor node via a message processor of the major
4 node.

1 35-43 (canceled)